

12 ch ECG



# Cardio7-S

\* Model name : Cardio7

**7" Color TFT LCD 12 Channel Interpretive Resting ECG with Touch Screen**

- \* Print out ECGs in multiple formats, including 12, 6 and 3 channel reports
- \* Supports USB Barcode Scanner & USB Memory Storage
- \* 12 channel interpretive ECG
- \* One-touch operation (monitoring, recording mode)
- \* Real-time preview monitor
- \* 12Ch simultaneous display
- \* Hi-Resolution color TFT LCD (800 x 480)
- \* Touch screen for easy operation
- \* Adaptable UI (Portrait & Landscape mode)
- \* Rotary key access to all menus
- \* No Cleaning  
Using disposable mouthpiece patented sensing method
- \* PRE-POST bronchodilator Comparison
- Over 130 kinds of interpretation results based on advanced Minnesota code
- Memory for up to 120 patients
- PC compatible through LAN
- Pacemaker detection
- Automatic arrhythmia detection
- HRV (Heart Rate Variability) Analysis
- 5 minute long term recording
- Pulmonary test with specialized theory
- Breathing Protocol
  - FVC (Forced Vital Capacity)
  - SVC (Slow Vital Capacity)
  - MVV (Maximum Voluntary Ventilation)
- Multi-language (English, Russian, French, German, Italian, Chinese, Spanish, Turkish, Polish, Romanian, Portuguese) available



**Bionet**

# SPECIFICATIONS

## ECG >>>

<b>ECG leads</b>	12 lead, 12 channel simultaneous ECG and acquisition
<b>Dimension</b>	296(W) × 305.5(H) × 92.5(D)mm, approx.3.5kg
<b>Recording channel</b>	3 channels + 1 rhythm, 3 channels + 3 rhythm, 6 channels + 1 rhythm, 12 channels, 60 seconds 1 channel, 5 minutes 1 channel and beat report
<b>Sensitivity</b>	2.5, 5, 10, 20, auto(I~aVF: 10, V1~V6: 5) mm/mV
<b>Printing speed</b>	12.5, 25, 50 mm/s
<b>Sampling rate</b>	500 samples/sec
<b>Filters</b>	AC(50/60 Hz, -20 dB or better) Muscle(25~35 Hz, -3 dB or better) Base line drift(0.1 Hz, -3 dB or better) Low pass filter : off, 40 Hz, 100 Hz, 150 Hz
<b>Display</b>	7" color TFT LCD display (800 x 480), 12 channels preview ECG wave
<b>Monitor display</b>	HR, ID, date, AC or Battery state, sensitivity, speed, number of saved data, printing form, rhythm lead
<b>User interface</b>	Touch screen (Alphanumeric and symbol available), Keyboard, rotary push-knob(pop-up menu)
<b>Patient data</b>	ID, name, age, sex, height, weight, smoke, race
<b>Basic measurement</b>	Heart rate, PR int, QRS dur, QT/QTc, P-R-T axis
<b>Recorder</b>	Thermal print head, roll paper Report papers : (width x length) - A4 : 215mm(8.5") x 297mm(11.7") - Letter : 215mm(8.5") x 280mm(11") Resolution - vertical : 8dot/mm - horizontal : 16dot/mm
<b>Electrical</b>	Resolution : 500 sample/sec. Internal noise: 20µV (p-p)max Input circuit : floating input Input impedance : ≥ 10M Ω Input voltage range : ≥ ± 5mV Common mode rejection : > 100 dB DC offset voltage : ≥ ± 300mV Time constant : 3.2sec Patient leakage current : < 10µA Frequency response : 0.05 ~ 150 Hz Isolated and defibrillation protected
<b>Signal quality control</b>	Disconnected lead detection, Pacemaker pulse detection
<b>ECG data storage</b>	storage for 120 ECGs (Internal on flash memory), USB flash drive
<b>Power</b>	Power supply : AC or built-in battery(option) 95 ~ 240 VAC, 50/60 Hz, 1.0 ~ 0.5A, 60W max
<b>Battery(Ni-MH)</b>	1 hour of normal use (approx. 100 ECG printouts)
<b>Communication</b>	PC connection with RS232 interface and LAN, USB Memory, USB Barcode Scanner
<b>Safety conformity</b>	Class I, Type BF, CE, FDA, KFSA, SFDA
<b>Environment</b>	Operating humidity : 30~85% Operating temperature : 10 ~ 40°C Atmospheric pressure : 70 ~ 106KPa
<b>Standard accessory</b>	Power cord 1 EA, Patient cable 1 EA, Limb 1 set(4 EA), Chest ball 1 set(6 EA), Chart paper 1 EA, Operation manual 1 EA
<b>Options</b>	Rechargeable battery, Cart, Hanger, Bag, PC S/W

## SPIROMETER >>>

<b>Dimension</b>	47(W) × 200(H) × 34(D)mm, approx.250g
<b>Measuring Values</b>	FVC: FVC, FEV 1.0, FEV 1/FVC, FEF 0.2-1.2L, FEF 25-75%, FEF 75-85%, PEF, FEF 25%, FEF 50%, FEF 75% SVC: SVC, ERV, IRV, TV, EC MVV: MVV, FB, TV
<b>Presentation</b>	Flow volume loop Flow time plot Measurement values table
<b>Measuring range</b>	Flow : 0 to ± 14 L/s Volume : 0 to ± 11L
<b>Measuring method</b>	Differential pressure method
<b>Prediction equation</b>	Morris-Polgar, ECCS-Quanjer, Knudson-ITS
<b>Sample rate</b>	200 samples/sec
<b>Flow impedance</b>	<0.2 mbar s/l at 12 l/s
<b>Measuring accuracy</b>	Complies with ATS (American Thoracic Society)
<b>Environment</b>	Ambient temperature : 15 to 40°C (59 to 104°F) Relative humidity : 10 to 90%(non-condensing) Atmospheric pressure : 700 to 1060hPa
<b>Standard accessory</b>	Nose clip 1 EA Adapter 2 EA Operation manual 1 EA Disposable mouthpiece 1 box(100 EA)

\* Specifications can be changed without prior notification.



شرکت ارکان آرا تجارت البرز

**North America (U.S.A): Bionet America, Inc.**

Tel: +1-714-734-1760  
E-mail: sales@BionetUS.com  
www.BionetUS.com

**South Korea: Bionet Co., Ltd.**

Tel: +82-70-7585-6418 (Int'l)/+82-2-6300-6483 (Domestic)  
E-mail: sales@ebionet.com (Int'l)/yunms@ebionet.com (Domestic)  
www.ebionet.com

**Latin America: Bionet Latin America, Inc.**

Tel: +1-949-800-9585  
E-mail: jayshim@ebionet.com  
www.ebionet.com

**Iran : Arkan Ara Tejarat Alborz Co., Ltd.**

Tel : +98-21-81060  
E-mail : info@arkanara.com  
www.arkanara.com