

12 ch ECG



Interpretive 12 Channel
Resting ECG

CardioCare 2000

- * Convenient A4 size print-outs allow for easy chart filing
- * Copy function allows varied printouts from single patient sample
- * Grid function allows you to use low cost plain fax paper
- * One-touch operation (monitoring, recording mode)
- * Accurate simultaneous 12 channel cardiac data acquisition
- Over 130 kinds of interpretation results based on advanced Minnesota code
- High-quality 12ch interpretive ECG at a 3ch price
- Free S/W upgrade via internet



Bionet

SPECIFICATIONS

ECG leads	12 lead, 12 channel simultaneous ECG and acquisition
Dimension	296 (W) X 305.5 (H) X 92.5 (D) mm, approx. 2,98 kg
Recording channel	3, 6, 12 channel and 1 channel (60 sec)
Sensitivity	5, 10, 20, auto (I-aVF:10, V1~V6:5) mm/mV
Printing speed	12.5, 25, 50 mm/s
Sampling rate	500 samples/sec
Filters	AC (50/60 Hz, -20 dB or better) Muscle (25 ~ 35 Hz, -3 dB or better) Base line drift (0.1 Hz, -3 dB or better) Low pass filter (off, 40 Hz, 100 Hz, 150 Hz)
Display	2 x 16 character LCD display
LCD display	Sensitivity, speed, filter status, HR, printing form, rhythm lead
LED indicator	Signal quality, power source, battery
Keyboard	Membrane keyboard, alphanumeric and symbol available
Patient Data	ID, name, age, sex, height, weight
Basic measurement	Heart rate, PR int, QRS dur, QT/QTc, P-R-T axis
Recorder	Thermal print head, roll paper Report papers: (width x length) - A4 : 215mm(8.5") x 297mm(11.7") - Letter : 215mm(8.5") x 280mm(11") Resolution - vertical:8 dot/mm - horizontal:16 dot/mm
Electrical	Internal noise:20 μ V(p-p)max Input circuit:Floating input Isolated and defibrillation protected Input impedance: \geq 10 M Ω Input voltage range: \geq \pm 5 mV Common Mode Rejection: \geq +100 dB DC offset voltage: \geq \pm 300 mV Time constant:3.2 sec Patient leakage current: < 10 μ A Frequency response 0.05 ~ 150 Hz
Signal quality control	Disconnected lead detection
Power	Power supply:AC or built-in battery (option) Power requirement:100 - 240 VAC, 50/60 Hz, 1.0 - 0.5 A Power consumption:60W max
Battery capacity	1 hour of normal use (approximately 100 automatic ECG printouts)
Communication	PC connection with RS-232 interface and LAN
Safety conformity	Class I, Type BF, CE, FDA, KFDA, CFDA
Environment	Operation humidity:30 ~ 85 % Operation Temperature:10 ° ~ 40 °C Atmospheric pressure:70 ~ 106 KPa
Standard accessory	Power cord 1 EA, Patient cable 1 EA, Limb 1 set(4 EA), Chest ball 1 set(6 EA), Chart paper 1 EA, Operation manual 1 EA
Options	Rechargeable battery, Cart, Hanger, Bag, PC S/W

* Specifications can be changed without prior notification.

شرکت ارکان آرا تجارت البرز

Iran : Arkan Ara Tejarat Alborz Co., Ltd.

Tel : +98-21-81060

E-mail : info@arkanara.com

www.arkanara.com

South Korea: Bionet Co., Ltd.

Tel: +82-70-7585-6418 (Int'l)/+82-2-6300-6483 (Domestic)

E-mail: sales@ebionet.com (Int'l)/ ajoy@ebionet.com (Domestic)

www.ebionet.com

Bionet

North America (U.S.A): Bionet America, Inc.

Tel: +1-714-734-1760

E-mail: sales@BionetUS.com

www.BionetUS.com

Latin America: Bionet Latin America, Inc.

Tel: +1-949-800-9585

E-mail: bla@ebionet.com

www.bionetesp.com